



CERTIFICATION LICENCE TO USE KEYMARK

Certificate No SKM 10209

DQS Hellas grants the present certificate to the enterprise:

SOLE S.A.

26, Amarousiou Chalandriou, 15125 Marousi

for the product:

Type of Solar Collectors Family:

SUPERSOL S200 (ECO S200), SUPERSOL S230 (ECO S230), SUPERSOL S260 (ECO S260)

which is produced in conformity with the normative document:

EN 12975-1:2011

EN ISO 9806:2017

at the following location:

Laikon Agonon & Lefktron, 13671 Acharnai



The present certificate is granted in accordance with:

- *the DQS Hellas General Rules for the Certification of Products,*
- *the Specific Rule for Certification EKIII.001 «Specific Rule for Certification of Solar Collectors, and Thermal Solar Heating Systems for Domestic Hot Water»,*
- *the Specific CEN Keymark Scheme Rules for Solar Thermal Products,*

and is ruled by the terms of the relevant contract between DQS Hellas and the enterprise.


Date of issue: **2024-11-20**

Date of valid: **2027-11-20**

Panagiotis Giannoutsos
Director of Certification

Dr. Emmanuel Deliyannakis
Managing Director



Annex to Solar Keymark Certificate					Licence Number		SKM 10209.1								
					Date issued		2024-11-28								
					Issued by		DQS Hellas								
Licence holder		SOLE S.A.			Country		GREECE								
Brand (optional)					Web		http://www.sole.gr								
Street, Number		Laikon Agonon & Lefktron			E-mail		info@sole.gr								
Postcode, City		13671 Acharnai			Tel		+30 210 2389500								
Collector Type					Flat plate collector										
Collector name					Gross area (A _G)	Gross length	Gross width	Gross height	Power output per collector G _b = 850 W/m ² , G _d = 150 W/m ² & u = 1.3 m/s θ _m - θ _a						
					m ²	mm	mm	mm	0 K	10 K	30 K	50 K	70 K	89 K	
SUPERSOL S200 (ECO S200)					1.88	1,960	960	82	1,455	1,389	1,237	1,059	854	635	
SUPERSOL S230 (ECO S230)					2.28	1,960	1,165	82	1,765	1,685	1,500	1,284	1,035	770	
SUPERSOL S260 (ECO S260)					2.64	2,135	1,238	82	2,043	1,950	1,737	1,486	1,199	891	
Power output per m ² gross area					774	739	658	563	454	338					
Performance parameters test method					Steady state - outdoor										
Performance parameters (related to A _G)					η ₀ , b	a1	a2	a3	a4	a5	a6	a7	a8	Kd	
Units					-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-	
Test results					0.782	3.34	0.018	0.000	0.00	10,630	0.000	0.00	0.0E+00	0.93	
Incidence angle modifier test method					Steady state - outdoor										
Incidence angle modifier					Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°	
Transversal					K _{GT,coil}	1.00	1.00	1.00	0.99	0.97	0.92	0.81	0.55	0.00	
Longitudinal					K _{GL,coil}	1.00	1.00	1.00	0.99	0.97	0.92	0.81	0.55	0.00	
Heat transfer medium for testing					Water										
Flow rate for testing (per gross area, A _G)					dm/dt		0.020	kg/(sm ²)							
Maximum temperature difference during thermal performance test					(θ _m -θ _a) _{max}		59	K							
Standard stagnation temperature (G = 1000 W/m ² ; θ _a = 30 °C)					θ _{stg}		197	°C							
Maximum operating temperature					θ _{max,op}		150	°C							
Maximum operating pressure					p _{max,op}		1500	kPa							
Testing laboratory		NCSR "DEMOKRITOS"			www.solar.demokritos.gr										
Test report(s)		4422 DE3 4423 DE1 4424 DQ1			Dated		28/11/24	10/10/24	10/10/24						
Comments					Ver. 6.2 (13.01.2022)										
The data was obtained from the test reports 4422 DE3 and 4424 DQ1					N.C.S.R. "DEMOKRITOS" SOLAR ENERGY LABORATORY Tel: +210 6503815 - Fax: +210 6544592 P.O. BOX 60037, 15310 Ag. Paraskevi, Greece										
Central Offices: Kalavriton 2, 145 64 kifisia, Athens, Tel: +301 6233493-4 , Fax: +301 6233495, http://www.dqsglobal.com, e-mail: i.alexou@dqs.gr															

Annex to Solar Keymark Certificate		Licence Number		SKM 10209.1											
Supplementary Information		Issued		2024-11-20											
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m															
Standard Locations		Athens		Davos		Stockholm		Würzburg							
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
SUPERSOL S200 (ECO S200)		2,372	1,727	1,132	1,826	1,272	791	1,342	888	532	1,459	963	568		
SUPERSOL S230 (ECO S230)		2,877	2,094	1,373	2,214	1,543	959	1,627	1,077	646	1,769	1,168	689		
SUPERSOL S260 (ECO S260)		3,331	2,425	1,589	2,564	1,786	1,110	1,884	1,247	748	2,049	1,352	798		
Gross Thermal Yield per m ² gross area		1,262	918	602	971	677	421	714	472	283	776	512	302		
Annual efficiency, η_a		71%	52%	34%	60%	42%	26%	61%	41%	24%	62%	41%	24%		
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)													
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²				
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C				
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°				
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/															
Additional Information															
Collector heat transfer medium										Water-Glycole					
The collector is deemed to be suitable for roof integration										No					
The collector was tested successfully under the following conditions:															
Climate class (A+, A, B or C)										A		--			
G (W/m ²) >		1000		ϑ_a (°C) >		20		H _x (MJ/m ²) >		600					
Maximum tested positive load										3000		Pa			
Maximum tested negative load										3000		Pa			
Hail resistance using steel ball (maximum drop height)										2		m			
Additional collector attribute(s)															
Using external power source(s) for normal operation										No		Active or passive measure(s) for self-protection		No	
Co-generating thermal and electrical power										No		Façade collector(s)		No	
Energy Labelling Information						Additional Informative Technical Data									
		Reference Area, A _{sol} (m ²)		Hydraulic Designation Code				Aperture Area, A _a (m ²)							
SUPERSOL S200 (ECO S200)		1.88		11-V-1234S-A:7.2-1892-C:16.6-1024				1.77							
SUPERSOL S230 (ECO S230)		2.28		14-V-1234S-A:7.2-1892-C:16.6-1226				2.17							
SUPERSOL S260 (ECO S260)		2.64		15-V-1234S-A:7.2-2067-C:16.6-1301				2.54							
Data required for CDR (EU) No 811/2013 - Reference Area						Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}									
Collector efficiency (η_{col})		61%				Zero-loss efficiency (η_0)		0.77		--					
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.						First-order coefficient (a ₁)		3.34		W/(m ² K)					
						Second-order coefficient (a ₂)		0.018		W/(m ² K ²)					
						Incidence angle modifier IAM (50°)		0.97		--					
						Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.									
Central Offices: Kalavriton 2, 145 64 kifisia, Athens, Tel: +301 6233493-4 , Fax: +301 6233495, http://www.dqsglobal.com , e-mail: i.alexou@dqs.gr															